

eBPF on FreeBSD

Hiroki Sato <hrs@FreeBSD.org>

FreeBSD Vendor/DevSummit 2019.10.12

2019/10/12 (c) Hiroki Sato

1

What is eBPF?

- ▶ BPF (Berkeley Packet Filter)
Steven McCanne, Van Jacobson: "The BSD Packet Filter: A New Architecture for User-level Packet Capture". USENIX, January 1993
- ▶ A virtual machine (software processor) designed for packet classification.
- ▶ Userland programs can use it via `/dev/bpf`.

BPF and Userland Applications

- ▶ Most of packet capturing software for BSD uses BPF. tcpdump (libpcap), dhclient, etc.
- ▶ Open /dev/bpf, bind an interface using ioctl (BIOCSETIF), and load a BPF program using ioctl (BIOCSETF).
- ▶ The userland program can read incoming/outgoing packets on the interface.

BPF in Kernel

- ▶ `struct ifnet` has `struct bpf_if *if_bpf`
- ▶ NIC device drivers call

`BPF_MTAP(struct bpf_if *, struct mbuf *)`

at the input and output routine.
- ▶ If a BPF file descriptor is attached, data in the mbuf will be evaluated by the registered BPF program.
- ▶ `bpf_filter()`

BPF in Kernel

```

hrs@phaleano % sudo tcpdump -d tcp and port 80
(000) ldh      [12]
(001) jeq      #0x86dd          jt 2    jf 8    12-byte offset, load 16 bits
(002) ldb      [20]
(003) jeq      #0x6             jt 4    jf 19   20-byte offset, load 8 bits
(004) ldh      [54]
(005) jeq      #0x50           jt 18   jf 6    54-byte offset, load 16 bits
(006) ldh      [56]
(007) jeq      #0x50           jt 18   jf 19   :
(008) jeq      #0x800          jt 9    jf 19   :
(009) ldb      [23]
(010) jeq      #0x6            jt 11   jf 19
(011) ldh      [20]
(012) jset     #0x1fff         jt 19   jf 13
(013) ldx      4*([14]&0xf)
(014) ldh      [x + 14]
(015) jeq      #0x50           jt 18   jf 16
(016) ldh      [x + 16]
(017) jeq      #0x50           jt 18   jf 19
(018) ret      #262144
(019) ret      #0

```


BPF in Kernel

```

hrs@phaleano % sudo tcpdump -d tcp and port 80
(000) ldh      [12]
(001) jeq      #0x86dd          jt 2    jf 8    12-byte offset, load 16 bits
(002) ldh      [20]
(003) j
(004) l
(005) j
(006) l
(007) j
(008) j
(009) l
(010) j
(011) l
(012) j
(013) l
(014) l
(015) jeq      #0x50           jt 18   jf 16
(016) ldh      [x + 16]
(017) jeq      #0x50           jt 18   jf 19
(018) ret      #262144
(019) ret      #0

```


ETHERNET II (DIX) FRAME



BPF in Kernel

```
hrs@phaleano % sudo tcpdump -d tcp and port 80
```

```
(000) ldh      [12]
(001) jeq     #0x86dd          jt 2    jf 8    12-byte offset, load 16 bits
(002) ldb     [20]
(003) jeq     #0x6            jt 4    jf 19   20-byte offset, load 8 bits
(004)
(005)
(006)
(007)
(008)
(009)
(010)
(011)
(012)
(013)
(014)
(015)
(016)
(017)
(018)
(019)
```



2019/10/12 (c) Hiroki Sato


7

BPF in Kernel

```
hrs@phaleano % sudo tcpdump -d tcp and port 80
```

```
(000) ldh      [12]
(001) jeq     #0x86dd          jt 2    jf 8    12-byte offset, load 16 bits
(002) ldb     [20]
(003) jeq     #0x6            jt 4    jf 19   20-byte offset, load 8 bits
(004) ldh     [54]
(005) jeq     #0x50            jt 18   jf 6    54-byte offset, load 16 bits
(006) ldh     [56]
(007) jeq     " "
(008) jeq     " "
(009) ldb     " "
(010) jeq     " "
(011) ldh     " "
(012) jset    " "
(013) ldx     " "
(014) ldh     " "
(015) jeq     " "
(016) ldh     " "
(017) jeq     " "
(018) ret
(019) ret
```

TCP header format



2019/10/12 (c)

8

BPF in Kernel

```
hrs@phaleano % sudo tcpdump -dd tcp and port 80
```

```
{ 0x28, 0, 0, 0x0000000c },  
{ 0x15, 0, 6, 0x000086dd },  
{ 0x30, 0, 0, 0x00000014 },  
{ 0x15, 0, 15, 0x00000006 },  
{ 0x28, 0, 0, 0x00000036 },  
{ 0x15, 12, 0, 0x00000050 },  
{ 0x28, 0, 0, 0x00000038 },  
{ 0x15, 10, 11, 0x00000050 },  
{ 0x15, 0, 10, 0x00000800 },  
{ 0x30, 0, 0, 0x00000017 },  
{ 0x15, 0, 8, 0x00000006 },  
{ 0x28, 0, 0, 0x00000014 },  
{ 0x45, 6, 0, 0x00001fff },  
{ 0xb1, 0, 0, 0x0000000e },  
{ 0x48, 0, 0, 0x0000000e },  
{ 0x15, 2, 0, 0x00000050 },  
{ 0x48, 0, 0, 0x00000010 },  
{ 0x15, 0, 1, 0x00000050 },  
{ 0x6, 0, 0, 0x00040000 },  
{ 0x6, 0, 0, 0x00000000 },
```

2019/10/12 (c) Hiroki Sato

9

BPF in Kernel

- ▶ `bpf_filter()` is an interpreter of the BPF instructions. 32-bit register x 16 + ACC + Index reg.
- ▶ The entry points are limited: `BPF_MTAP()` calls `bpf_filter()` to classify data in the mbufs.
- ▶ There is no API to call a BPF program, or to call a kernel function from a BPF program.

2019/10/12 (c) Hiroki Sato

10

eBPF

- ▶ An extended version of BPF virtual machine (Linux 4.16 or later).
- ▶ 64-bit registers x 10, 512 bytes stack, and key-value store. A function call instruction.
- ▶ General purpose, not limited to as a packet classifier---it can communicate with other subsystem or userland via the key-value store or function call.
- ▶ Addresses for the function calls and key-value store are resolved at loading time.

eBPF function call

- ▶ Function pointers are relocated at loading time.
- ▶ Although "call" instruction has a jump target address, eBPF interpreter does not allow an arbitrary address.
- ▶ Limited to "pre-registered kernel helper functions".

eBPF Map

- ▶ Key-value store data structure which can be accessed by eBPF program, kernel subsystem, and userland program. Statically pre-allocated before running a program.
- ▶ Array, Hash, address table, etc
- ▶ eBPF programs use kernel helper functions to access them. Other kernel subsystems can read/write data by using the same function set.
- ▶ Userland program can read/write the data structure by `ioctl(2)`, which eventually calls the same function set.

eBPF on FreeBSD

- ▶ I and Yutaro Hayakawa, GSoC student in 2018, have maintained an implementation for FreeBSD at <https://github.com/YutaroHayakawa/generic-ebpf>
 - ▶ [Current status]
 - ▶ eBPF interpreter and JIT compiler
 - ▶ Map helper functions
 - ▶ Userland interface (`/dev/ebpf` and `ioctls`)
 - ▶ Still lacking of...
 - ▶ hooks in kernel.
 - ▶ helper functions other than map access.

Use of eBPF

Development

- ▶ eBPF in assembly language is pain. An eBPF program can be written in a C-like language:
make WITH_LLVM_TARGET_BPF=yes buildworld (?)
<https://reviews.freebsd.org/D16033>
- ▶ `% clang80 -target bpf -c -o foo.o foo.c`
- ▶ ELF sections for eBPF maps and hints for relocation.

```
hrs@phaleano % cat foo.c
```

```
#include <stdint.h>

uint64_t glob64;

int
main(void)
{
    int a;

    a = 2;

    return (a + 1);
}
```

```
hrs@phaleano % llvm-objdump80 -x --disassemble foo.o
```

```
foo.o: file format ELF64-BPF
```

```
architecture: bpfel
```

```
start address: 0x0000000000000000
```

```
Disassembly of section .text:
```

```
0000000000000000 main:
```

```
0:      b7 01 00 00 00 00 00 00      r1 = 0
1:      63 1a fc ff 00 00 00 00      *(u32 *)(r10 - 4) = r1
2:      b7 01 00 00 02 00 00 00      r1 = 2
3:      63 1a f8 ff 00 00 00 00      *(u32 *)(r10 - 8) = r1
4:      61 a1 f8 ff 00 00 00 00      r1 = *(u32 *)(r10 - 8)
5:      07 01 00 00 01 00 00 00      r1 += 1
6:      bf 10 00 00 00 00 00 00      r0 = r1
7:      95 00 00 00 00 00 00 00      exit
```

```
Sections:
```

Idx	Name	Size	Address	Type
0		00000000	0000000000000000	
1	.strtab	00000045	0000000000000000	
2	.text	00000040	0000000000000000	TEXT
3	.BTF	00000019	0000000000000000	
4	.BTF.ext	00000020	0000000000000000	
5	.llvm_addrsig	00000000	0000000000000000	
6	.symtab	00000060	0000000000000000	

```
2019/10/12 (c) Hiroki Sato  
SYMBOL TABLE:
```

17

Use of eBPF

Entry Points

- ▶ An eBPF program can be invoked in kernel:
ebpf_vm_alloc(), ebpf_load_prog(), and ebpf_vm_run()
- ▶ With helper functions, a userland program can inject an eBPF program, make it do something in kernel, and get a result via map data structure.
- ▶ It is possible to add a hook into the existing execution path just like DTrace's probe.

Benefits

- ▶ **Q:** Why a new vm/language? Developing a kernel module in C language looks easier.
- ▶ **A:** It works well where flexibility in kernel depending on data is required:
 - ▶ Packet filtering based on rules,
 - ▶ Patching a syscall from userland for security purpose
 - ▶ L2 packet forwarding (learning bridge) w/o entering the kernel network stack,
 - ▶ cf. Netgraph subsystem: collections of klds to process mbufs.

Discussions (1)

- ▶ Actual use cases? Linux uses eBPF as
 - ▶ a packet processing state machine.
 - ▶ a tool for tracing and filtering syscalls.
 - ▶ bpftrace: ebpf-backed DTrace clone
- ▶ Entry points and helper functions for eBPF programs in kernel depends on the application:
 - ▶ Possible to attach to socket, if_input/output, syscall entry, etc.
 - ▶ Provides efficiency to "traversing a tree and compare"--- e.g. compiling IPsec SPD/SAD into eBPF code.

Discussions (2)

- ▶ Safety of an eBPF program. Linux implements an in-kernel code verification based on simulating execution paths and pointer arithmetics.
 - too complex. Verification in userland instead?
- ▶ Program compatibility with Linux eBPF?
 - ▶ Same kernel helper functions and map structures.
 - ▶ It uses (struct sk_buff)-specific helper functions.

Questions?

- ▶ <https://github.com/YutaroHayakawa/generic-ebpf>
- ▶ <https://people.freebsd.org/~hrs/hrs-20191012-ebpf.pdf>
- ▶ hrs@FreeBSD.org